

SURAT SMARTCITY DEVELOPMENT LTD (SSCDL)

Name of Work :- Selection of service Provider for Procurement, Supply, Integration and Maintenance of various Hardware Components for Intelligent Transit Management System (ITMS) for Bus Rapid Transit System (BRTS) and City Bus Operation for Surat City for Surat Municipal Corporation, Surat (3rd Attempt)

Ref :- Tender Notice No.: GM(IT)/BRTS/ITMS/02/2017-2018

ADDENDA/CORRIGENDUM - I

- A. The bidders are requested to take note of the following changes and / or additions made in the RFP documents which are to be taken in to consideration while submitting their bid. They shall be presumed to have done so and accordingly submitted with their Bid.
- B. The ADDENDA/CORRIGENDUM-1 duly signed by the bidders at the relevant space provided for the purpose shall be returned with the Technical bid of the tender.
- C. The ADDENDA/CORRIGENDUM shall be treated as the part of the tender documents.

Sr. No.	AS PER / In RFP documents			Has been changed/ Amended and now shall be read as under		
1	Clause 1.6 : Schedule of Bidding Process			The Clause1 .6 : Schedule of Bidding Process has been changed and now read as under		
	Sr. No.	Event Description	Date , Time and Address	Sr. No.	Event Description	Date , Time and Address
	1	Downloading of RFP Documents	07/ 09/2017 to 16/09/2017 up to 18:00 hrs.from website https://smc.nprocure.com .	1	Downloading of RFP Documents	07/ 09/2017 to 25/09/2017 up to 18:00 hrs. from website https://smc.nprocure.com .
	4	Due date for Technical and Price Bid Submission (Online through E-Tendering) (Bid Due Date/Bid Submission Date)	on or before 16/09/2017 up to 18:00 hrs through website https://smc.nprocure.com . The Bids of Bidder submitting Technical and Price Bid (or either of Technical or Price Bid) in Physical Format in Hard Copy shall be treated as non responsive and rejected.	4	Due date for Technical and Price Bid Submission (Online through E-Tendering) (Bid Due Date/Bid Submission Date)	on or before 25/09/2017 up to 18:00 hrs through website https://smc.nprocure.com . The Bids of Bidder submitting Technical and Price Bid (or either of Technical or Price Bid) in Physical Format in Hard Copy shall be treated as non responsive and rejected.
	5	Date of physical submission of RFP Fee, EMD and Affidavit (Original) through Post/Speed Post/RPAD only	After 16/09/2017 and On or before 20/09/2017 upto 17:00 hrs by Post/Speed Post/RAPD only at following address Chief Accountant, Surat Municipal Corporation, Muglisara, Surat-395003. The Bids of the Bidder submitting Original of RFP Fees /EMD/Affidavit beyond the period specified in first para and or through courier/hand delivery shall be rejected as non responsive.	5	Date of physical submission of RFP Fee, EMD and Affidavit (Original) through Post/Speed Post/RPAD only	On or before 03/10/2017 upto 17:00 hrs by Post/Speed Post/RAPD only at following address Chief Accountant, Surat Municipal Corporation, Muglisara, Surat-395003. The Bids of the Bidder submitting Original of RFP Fees /EMD/Affidavit beyond the period specified in first para and or through courier/hand delivery shall be rejected as non responsive.

2	<p>Appendix-8, Section 3 (page no 15) : Environment Specifications of BRT /HMC station/Terminal LED TV based PIS Display System.</p> <table border="1" data-bbox="256 302 1073 501"> <thead> <tr> <th>Sr. No</th> <th>Parameter</th> <th>Min. Requirement</th> </tr> </thead> <tbody> <tr> <td>3</td> <td>Environmental specifications</td> <td>Temperature: 0 to +55 deg C; Sealing: IP 65 (Front), IP 54 (Rear) Humidity: 95% RH, Industrial Grade</td> </tr> </tbody> </table>	Sr. No	Parameter	Min. Requirement	3	Environmental specifications	Temperature: 0 to +55 deg C; Sealing: IP 65 (Front), IP 54 (Rear) Humidity: 95% RH, Industrial Grade	<p>Appendix-8, Section 3 (page no 15) : Environment Specifications of BRT /HMC station/Terminal LED TV based PIS Display System has been changed and now read as under .</p> <table border="1" data-bbox="1096 302 1908 626"> <thead> <tr> <th>Sr. No</th> <th>Parameter</th> <th>Min. Requirement</th> </tr> </thead> <tbody> <tr> <td>3</td> <td>Environmental specifications</td> <td>Temperature: 0 to +55 deg C; Sealing: IP 65 (Front), IP 54 (Rear). Humidity: 95% RH, Industrial Grade. Casing is acceptable in case IP 65 & IP 54 protection is provided and all other operating parameters as above are met.</td> </tr> </tbody> </table>	Sr. No	Parameter	Min. Requirement	3	Environmental specifications	Temperature: 0 to +55 deg C; Sealing: IP 65 (Front), IP 54 (Rear). Humidity: 95% RH, Industrial Grade. Casing is acceptable in case IP 65 & IP 54 protection is provided and all other operating parameters as above are met.																						
Sr. No	Parameter	Min. Requirement																																		
3	Environmental specifications	Temperature: 0 to +55 deg C; Sealing: IP 65 (Front), IP 54 (Rear) Humidity: 95% RH, Industrial Grade																																		
Sr. No	Parameter	Min. Requirement																																		
3	Environmental specifications	Temperature: 0 to +55 deg C; Sealing: IP 65 (Front), IP 54 (Rear). Humidity: 95% RH, Industrial Grade. Casing is acceptable in case IP 65 & IP 54 protection is provided and all other operating parameters as above are met.																																		
3	<p>Appendix-8, Section 3 (page no 20) : Specification for UPS for BRT Bus Station</p> <table border="1" data-bbox="256 716 1073 886"> <thead> <tr> <th>Sr. No</th> <th>Description</th> <th>Min. Required Specification</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>Rating (in KVA)</td> <td>1 KVA</td> </tr> <tr> <td></td> <td>[F] Battery</td> <td></td> </tr> <tr> <td>2</td> <td>DC Voltage</td> <td>36 V</td> </tr> </tbody> </table>	Sr. No	Description	Min. Required Specification	1	Rating (in KVA)	1 KVA		[F] Battery		2	DC Voltage	36 V	<p>Appendix-8, Section 3 (page no 20) : Following Specification for UPS for BRT Bus Station has been changed and now read as under.</p> <table border="1" data-bbox="1096 716 1908 886"> <thead> <tr> <th>Sr. No</th> <th>Description</th> <th>Min. Required Specification</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>Rating (in KVA)</td> <td>2 KVA with 4 hour battery backup</td> </tr> <tr> <td></td> <td>[F] Battery</td> <td></td> </tr> <tr> <td>2</td> <td>DC Voltage</td> <td>Up to 96 V</td> </tr> </tbody> </table>	Sr. No	Description	Min. Required Specification	1	Rating (in KVA)	2 KVA with 4 hour battery backup		[F] Battery		2	DC Voltage	Up to 96 V										
Sr. No	Description	Min. Required Specification																																		
1	Rating (in KVA)	1 KVA																																		
	[F] Battery																																			
2	DC Voltage	36 V																																		
Sr. No	Description	Min. Required Specification																																		
1	Rating (in KVA)	2 KVA with 4 hour battery backup																																		
	[F] Battery																																			
2	DC Voltage	Up to 96 V																																		
4	<p>Appendix-8, Section 3 (page no 23-24) : Station Server Specification (To be used at Terminal)</p> <table border="1" data-bbox="256 992 1073 1032"> <tr> <td>Expansion</td> <td>MIOe</td> <td>1</td> </tr> </table>	Expansion	MIOe	1	<p>Appendix-8, Section 3 (page no 23-24) : Following Specification of Station Server Specification (To be used at Terminal)</p> <table border="1" data-bbox="1096 992 1864 1065"> <tr> <td>Expansion</td> <td>MIOe requirement is optional</td> <td>1 .</td> </tr> </table>	Expansion	MIOe requirement is optional	1 .																												
Expansion	MIOe	1																																		
Expansion	MIOe requirement is optional	1 .																																		
5	<p>Appendix-9 : Service Levels for Depot Management Hardware (Sr.No. 5) (page no. 86).</p> <table border="1" data-bbox="256 1175 1073 1408"> <thead> <tr> <th rowspan="2">sr. No</th> <th rowspan="2">Project Component</th> <th rowspan="2">Service Level Description –</th> <th rowspan="2">Measuring Duration</th> <th colspan="3">Availability</th> </tr> <tr> <th>Baseline Minimum</th> <th>Lower Performance</th> <th>Critical Breach</th> </tr> </thead> <tbody> <tr> <td>5</td> <td>Depot Mgt Hardware</td> <td>Availability of Hardware</td> <td>Daily</td> <td>99.94% to 98%</td> <td>< 98%</td> <td>99.95 %</td> </tr> </tbody> </table>	sr. No	Project Component	Service Level Description –	Measuring Duration	Availability			Baseline Minimum	Lower Performance	Critical Breach	5	Depot Mgt Hardware	Availability of Hardware	Daily	99.94% to 98%	< 98%	99.95 %	<p>Appendix-9 : Service Levels for Depot Management Hardware (Sr.No. 5) (page no. 86). has been changed and now read as under.</p> <table border="1" data-bbox="1096 1175 1908 1416"> <thead> <tr> <th rowspan="2">sr. No</th> <th rowspan="2">Project Component</th> <th rowspan="2">Service Level Description –</th> <th rowspan="2">Measuring Duration</th> <th colspan="3">Availability</th> </tr> <tr> <th>Baseline Minimum</th> <th>Lower Performance</th> <th>Critical Breach</th> </tr> </thead> <tbody> <tr> <td>5</td> <td>Depot Mgt Hardware</td> <td>Availability of</td> <td>Daily</td> <td>99.94% to 98%</td> <td>< 98%</td> <td><97%</td> </tr> </tbody> </table>	sr. No	Project Component	Service Level Description –	Measuring Duration	Availability			Baseline Minimum	Lower Performance	Critical Breach	5	Depot Mgt Hardware	Availability of	Daily	99.94% to 98%	< 98%	<97%
sr. No	Project Component					Service Level Description –	Measuring Duration	Availability																												
		Baseline Minimum	Lower Performance	Critical Breach																																
5	Depot Mgt Hardware	Availability of Hardware	Daily	99.94% to 98%	< 98%	99.95 %																														
sr. No	Project Component	Service Level Description –	Measuring Duration	Availability																																
				Baseline Minimum	Lower Performance	Critical Breach																														
5	Depot Mgt Hardware	Availability of	Daily	99.94% to 98%	< 98%	<97%																														

7	<p>Appendix 3: PROFORMA OF BANK GUARANTEE FOR BID SECURITY (Page -66) ...which expression shall unless it be repugnant to the subject or context hereof be deemed to include its successors and assigns) in favour of Surat Municipal Corporation having its Office at _____(hereinafter referred to as “SSCDL”...</p>	<p>Appendix 3: PROFORMA OF BANK GUARANTEE FOR BID SECURITY (Page -66) shall be read and replaced as follows ...which expression shall unless it be repugnant to the subject or context hereof be deemed to include its successors and assigns) in favour of Surat Smartcity Development Ltd having its Office at _____(hereinafter referred to as “SSCDL”...</p>
---	--	--

Note : All other terms, conditions and specifications other than the changes made under this Addenda/Corrigendum shall remain unchanged and shall be the part of the tender/RFP document.

General Manager (IT)
Surat Smart City Development Ltd.

Signature of Bidder.

Date :

Place :